Guangzhou YuBen Hydraulic Technology Co., Ltd

Add: A5 Factory, Lanyuan Industrial Zone, No. 8 Xinwu Sixth Street, Zhaidong Village, Yongning Street, Zengcheng District, Guangzhou



YB-P18X FEATURES


P18X hose-crimping machine has been designed to crimp up to 3/4" diameter 4-spiral hoses. It is small hydraulic crimping machine for repair workshops and field use. Easy to use, light and compact in size.

STANARD FEATURES

※Foot pedal

CONTROL ※Semi-Automatic

Dies:				
DieSetNo	Crimping range	ID (mm)	L (mm)	
P18/06*	6.0 - 8.0	6	55	
P18/08*	8.0 - 10.0	8	55	
P18/12*	12.0 - 14.0	12	55	
P18/14	14.0 - 16.0	14	55	
P18/16	16.0 - 19.0	16	55	
P18/19	19.0 - 23.0	19	55	
P18/23	23.0 - 27.0	23	55	
P18/27	27.0 - 31.0	27	65	
P18/31	31.0 - 36.0	31	65	
P18/36	36.0 - 41.0	36	65	
P18/41	41.0 - 47.0	41	65	
*: Non standard die				



TECHNICAL DATA		
Max crimping dia (mm)	10-54	
Max crimping dia (inches)	0.39-2.13	
Max. crimping force (kN)	800	
Max. crimping force (tonnage)	80	
Cycle time 10 mm (s)		
Hose size ID (inches)	3/4(4sp) / 1(2sp)	
Dies set series	P18	
Max. opening (mm)	+20	
Max.opening without dies (mm)	68	
Master die D / L (mm)	48/64	
Master die D / L (inches)	1.89/2.52	
Motor Power	2.2 kW	
Oil tank volume (L)	26	
Crimping /hour		
Motor Voltage (V): Tri	200/220/380	

DIMENSIONS (L x W x H)	
Machine (mm)	600X355X585
Machine (inch)	23.62X13.98X23.03
Package (mm)	680X550X680
Package (inch)	26.77X21.65X26.77
WEIGHT (KG)	
N, W.	76
G.W.	91