
Guangzhou YuBen Hydraulic Technology Co., Ltd

Add: A5 Factory, Lanyuan Industrial Zone, No. 8 Xinwu Sixth Street, Zhaidong Village, Yongning Street, Zengcheng District, Guangzhou





Yuben P32CS hose-crimping machine has been designed to crimp up to 2" diameter4spiral hoses. It is fast and easy to use. And for car-service use. It is fast and easy to use. CS machines are battery powered with 12V or 24V.



TECHNICAL DA	ТА		P32Dies:			
Max crimping dia (mm)		10-87	DieSetNo	Crimping range	ID (mm)	L (mm)
Max crimping dia (inches)		0.39-3.42	P32/06*	6.0 - 8.0	6	55
Max. crimping force (kN)		2000	P32/08*	8.0 - 10.0	8	55
Max. crimping force (tonnage)		200	P32/10*	10.0 - 12.0	10	55
Cycle time 10 mm (s)		7.5	P32/12*	12.0 - 14.0	12	55
Hose size ID (inches)		2" (4SH) /11/2"(6SH)	P32/14*	14.0 - 16.0	14	55
Dies set series		P32	P32/16	16.0 - 19.0	16	55
Max. opening (mm)		+33	P32/19	19.0 - 22.0	19	55
Max.opening without dies (mm)		132	P32/22	22.0 - 26.0	22	70
Master die D/L (mm)		99/80	P32/26	26.0 - 30.0	26	70
Master die D/L (inches)		3.90/3.15	P32/30	30.0 - 34.0	30	70
Motor (kW) 12V/24V		1.6/2.25	P32/34	34.0 - 39.0	34	75
Motor (HP) 12V/24V		2.1/3.05	P32/39	39.0 - 45.0	39	75
Oil tank volume (L)		4	P32/45	45.0 - 51.0	45	90
Crimping /hour		100	P32/51	51.0 - 57.0	51	90
			P32/57	57.0 -63.0	57	100
DIMENSIONS (L x W x H)		STANARD FEATURES	P32/63	63.0 - 69.0	63	100
Machine (mm)	600X480X520	XQuickChange-tool	P32/69	69.0 - 75.0	69	100
Machine (inch)	23.6X18.9X20.5	XDie wall racks	P32/74*	74.0 - 80.0	74	100
•••	830X630X600		P32/78*	78.0 - 87.0	78	100
Package (mm) Package (inch)	32.7X24.8X23.6	OPTIONS	*: Non standard die			
WEIGHT (KG)		※Foot pedal				/DE SIZE
N, W.	143	1		8		1 and
G.W.	178	A	ante is	B B		opt
CONTROL ※Semi-Automatic		and and the set	Landiad.		ode /	Do
				- Contraction - Contraction	Son Yol	o
		And a state of the		8	18	B
			Service and the service of the servi	L	~d_/	