

## Guangzhou YuBen Hydraulic Technology Co., Ltd

Add: A5 Factory, Lanyuan Industrial Zone, No. 8 Xinwu Sixth Street, Zhaidong Village, Yongning Street, Zengcheng District, Guangzhou




## YB-P20CSZ FEATURES







Yuben P20CSZ hose-crimping machine has been designed to crimp up to 1 1/2" diameter 4 -spiral hoses . And for car-serviceuse. It is fast and easy to use. CS achines are battery powered with 12V or 24V



TECHNICAL DATA	
Max crimping dia (mm)	10-61
Max crimping dia (inches)	0.39-2.40
Max. crimping force (kN)	1370
Max. crimping force (tonnage)	137
Cycle time 10 mm (s)	7.2
Hose size ID (inches)	11/2(2SN) / 11/4(4SP)
Dies set series	P20
Max. opening (mm)	+25
Max.opening without dies (mm)	109
Master die D / L (mm)	84/80
Master die D/L (inches)	3.31/3.15
Motor (kW) 12V/24V:	1.6/2.25
Motor (HP) 12V/24V:	2.1/3.05
Oil tank volume (L)	4
Crimping /hour	200

DIMENSIONS (L x W x H)			
Machine (mm)	600X480X480		
Machine (inch)	23.6X18.9X18.9		
Package (mm)	830X630X600		
Package (inch)	32.7X24.8X23.6		

WEIGHT (KG)	
Machine N.W.	120
Machine G.W.	145

STANARD FEATURES
<b>XQuickChange-tool</b>
<b></b> XDie wall racks
OPTIONS
<b></b> XFoot pedal
CONTROL
<b>XSemi-Automatic</b>

P20 Dies:				
DieSetNo	Crimping range	ID (mm)	L (mm)	
P20/06*	6.0-8.0	6	55	
P20/08*	8.0-10.0	8	55	
P20/10*	10.0-12.0	10	55	
P20/12*	12.0-14.0	12	55	
P20/14	14.0-16.0	14	55	
P20/16	16.0-19.0	16	55	
P20/19	19.0-23.0	19	55	
P20/23	23.0-27.0	23	55	
P20/27	27.0-31.0	27	70	
P20/31	31.0-36.0	31	70	
P20/36	36.0-41.0	36	75	
P20/41	41.0-47.0	41	75	
P20/47	47.0-52.0	47	85	
P20/52*	52.0-60.0	52	85	
*: Non standard die				

