



YB-NC20 FEATURE



YUBEN NC machine provide fast and accurate crimping for fitting manufacturing. Crimping range is 12-49 mm.



CONTROL

- ※Semi-Automatic
- ※Automatic

YB-NC20

TECHNICAL DATA

Max crimping dia (mm)	12-49
Max crimping dia (inches)	0.47-1.93
Max. crimping force (kN)	500
Max. crimping force (Tonnage)	50
Cycle time 10 mm (s)	1.5
Hose size ID (inches)	1 1/4"
Dies set series	NC30
Max. opening (mm)	+18
Max. opening without dies (mm)	117
Master die D / L (mm)	99/22
Master die D / L (inches)	3.90/0.87
Motor Tri/Mono (kW/HP)	3.0/4.0
Oil tank volume (L)	50
Motor Voltage (V): Tri	200/220/380/440
Motor Voltage (V): Mono	220/230/240

DIMENSIONS (L x W x H)

Machine (mm)	820X750X1030
Machine (inch)	32.3X29.5X40.6
Package (mm)	925X925X1220
Package (inch)	36.4X36.4X48.0

WEIGHT (KG)

N.W.	287
G.W.	317

NC30 Dies:

DieSetNo	Crimping range	ID (mm)	L (mm)
NC30/12	12.0-16.0	12	3
NC30/16	16.0-22.0	16	4
NC30/22	22.0-26.0	22	4.5
NC30/26	26.0-34.0	26	5
NC30/34	34.0-39.0	34	5
NC30/39	39.0-49.0	39	5

*: Non standard die

